



Robust and stable

UNIVERSAL RIFLE MOUNT STAND type 681-550 and Azimuth/Elevation Mount type 681-400




The Universal Weapon Rest Type 681-600 series is designed to clamp firmly a wide range of small arms for remote firing (see separate leaflet).

If orthogonal firing is required for ballistics material testing, then it is mounted on the X/Y mount type 681-1200, however it is more normally fitted to the Azimuth/Elevation Mount type 681-400 (see right-hand image above) which is secured to the Stand type 681-550 (see left-hand image above).

SPECIFICATION

Unit	Calibre	Size	Movement	Weight
Stand Type 681-550	All calibres up to 40mm	Height: 670mm Width: 1040mm Depth: 1040mm		170kg
Azimuth/Elevation Mount Type 681-400	All calibres up to 14.5mm	Height: 595mm Width: 510mm Depth: 1180mm	5 degrees left-right 5 degrees up-down	175kg



MS INSTRUMENTS Range Consultancy

Precision, Expertise, Quality

- Professional Bespoke Range Designs
- State-of-the-Art Product Rendering
- Only the Latest Standards



MS Instruments Ltd.

Unit 4, Ravensquay Business Centre, Cray Avenue
Orpington, Kent, BR5 4BQ, United Kingdom
Tel: +44 (0)1689 883 020
Fax: +44 (0)1689 871 392
contact@msinstruments.co.uk
www.msinstruments.co.uk

ISO 9001 SCS cert. No. 980010
681-550-universal-riflemount-stand-and-az-el - Apr-21

The information in this document is correct at the stated time. MS Instruments Ltd has a policy of continuing development and reserves the right to make design changes/improvements to the products.